

POINT ANCHOR SYSTEM



Double Lok

Minova's Double Lok Bolt is state-of-the-art for both anchorage and speed. It boasts a double benefit and provides more control at a lower cost.

The Double Lok Bolt does not require any special tools or installation techniques. Instead, when used with the proper Minova resin, the expansion shell of the Double Lok Bolt sets the initial anchorage and allows the resin to cure in a state of compression.

Additional anchorage for this system takes place along the interface of the bolt shaft, resin and bore-hole wall. The "combination anchorage" of the expansion shell and resin has proven very successful for adverse ground conditions.

Installation Procedures:

1. Drill hole at proper diameter and depth.
2. Make depth 2" longer than the bolt.
3. Insert appropriate Minova resin cartridge.
4. Insert Double Lok Bolt and Bearing Plate to within 1/16" to 1/8" of roofline.
5. Rotate bolt using drill pre-set to proper torque. Bearing Plate should be tight against roof.

Specifications:

Bar Diameter & Grade	Min Yield	Min Tensile	Borehole	Shell	Plate	ft-lbs
#5 (16 mm) Gr60	13,600 lbs	20,300 lbs	1"	Standard	Gr2	125 - 225
5/8" SRD Gr75	17,000 lbs	22,600 lbs	1"	Standard	Gr2	125 - 225
#6 (19 mm) Gr40	13,400 lbs	23,400 lbs	1-3/8"	Standard, Long	Gr3, Gr4	125 - 225
#6 (19 mm) Gr60	20,000 lbs	30,100 lbs	1-3/8"	Standard, Long	Gr3, Gr4	150 - 275
3/4" SRD Gr75	25,100 lbs	33,400 lbs	1-3/8"	Standard, Long	Gr3, Gr4	175 - 300
#7 (22 mm) Gr40	18,500 lbs	32,300 lbs	1-3/8"	Standard	Gr3, Gr4	175 - 300
#7 (22 mm) Gr60	27,700 lbs	41,600 lbs	1-3/8"	Standard	Gr3, Gr4	200 - 350
7/8" SRD Gr75	34,700 lbs	46,200 lbs	1-3/8"	Standard	Gr3, Gr4	250 - 375



Solutions from Materials Technology



Minova USA Inc. Products

Bolts and Plates

Anchoring Products

Pumpable Cementitious Grouts

Airtite® Sealants and Coatings

Chemical Grouts

Manufactured and sold under license from Minova International Limited.

Minova USA Inc.
150 Carley Court
Georgetown, KY 40324 USA
Phone 502 863 6800
Fax 502 863 1374

Email sales.info@minovaint.com
Website www.minovausa.com



A member of the Orica Group

Important Note: Warranty

Minova USA Inc. warrants that its products, at the time of shipment, conform to the applicable descriptions set forth in the invoice and are free from defects in material and workmanship. NO OTHER WARRANTY, WHETHER EXPRESS, IMPLIED OR STATUTORY, INCLUDING ANY WARRANTY OF MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE, SHALL EXIST IN CONNECTION WITH THE SALE OR USE OF ANY MINOVA USA INC. PRODUCT, AND ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED AND EXCLUDED.

All claims under this warranty must be made in writing to Minova USA Inc. within 15 days after discovery of the defect, and within 90 days of the date of shipment by Minova USA Inc. of the product claimed defective. Upon timely receipt of a claim, Minova USA Inc. shall have the option either to inspect the product while in Buyer's possession or to request Buyer to return the product to Minova USA Inc. for inspection. Claims not made as provided above and within the applicable time period will be barred. All warranties shall be null and void if the products have not been stored and used in accordance with procedures recommended by Minova USA Inc.

Minova USA Inc. shall, at its option, either replace the nonconforming or defective product or refund to Buyer its purchase price. The foregoing constitutes Buyer's sole and exclusive remedy for any breach or warranty.